PEEK® spacer of hexagon shape

3MPP, 4MPP series (20pcs/pack)

• This material has excellent heat resistance and chemical resistance properties.

• Material: PEEK® (UL94V-0)

• Color: BROWN

• Operating temperature range: - 40 to + 200℃


■ 3MPP type (for M3)


- om r typo (ror mo)			
Part No.	А	L	
3MPP-4	Through hole	4	
3MPP-5	Through hole	5	
3MPP-6	Through hole	6	
3MPP-7	Through hole	7	
3MPP-8	Through hole	8	
3MPP-9	Through hole	9	
3MPP-10	Through hole	10	
3MPP-11	Through hole	11	
3MPP-12	Through hole	12	
3MPP-13	Through hole	13	
3MPP-14	Through hole	14	
3MPP-15	6 or over	15	
3MPP-16	6 or over	16	
3MPP-17	6 or over	17	
3MPP-18	6 or over	18	
3MPP-19	6 or over	19	
3MPP-20	6 or over	20	
3MPP-25	6 or over	25	
3MPP-30	6 or over	30	

■ 4MPP type (for M4)

Part No.	А	L
4MPP-4	Through hole	4
4MPP-5	Through hole	5
4MPP-6	Through hole	6
4MPP-7	Through hole	7
4MPP-8	Through hole	8
4MPP-9	Through hole	9
4MPP-10	Through hole	10
4MPP-11	Through hole	11
4MPP-12	Through hole	12
4MPP-13	Through hole	13
4MPP-14	Through hole	14
4MPP-15	Through hole	15
4MPP-16	Through hole	16
4MPP-17	Through hole	17
4MPP-18	8 or over	18
4MPP-19	8 or over	19
4MPP-20	8 or over	20
4MPP-25	8 or over	25
4MPP-30	8 or over	30







PEEK® screw, nut

MPE series (20pcs/pack)


• This screw has excellent heat resistance and chemical resistance properties.

• Material:PEEK® (UL94V-0)


• Color: Brown

• Operating temperature range: - 40 to + 200℃







Part No.	L
2MPE-4	4
2MPE-5	5
2MPE-6	6
2MPE-8	8
2MPE-10	10




Part No.	L
2.6MPE-6	6
2.6MPE-8	8
2.6MPE-10	10
2.6MPE-12	12



Part No.	L
3MPE-6	6
3MPE-8	8
3MPE-10	10
3MPE-12	12
3MPE-16	16
3MPE-20	20



Part No.	L
4MPE-6	6
4MPE-8	8
4MPE-10	10
4MPE-12	12
4MPE-16	16
4MPE-20	20
4MPE-25	25



Part No.	А	В	С
3MPE-N	5.5	2.4	М3
4MPE-N	7	3.2	M4

^{*} PEEK is the registered trade mark of Victrex-MC, Inc.