



**Connected terminal for mounting socket electric wire**

**ON series (10pcs/pack)**


- This is a male pin connected type for fitting the connection socket PM series (2.54 mm pitch type).
- This is used for taking out the signal by the electric wire from PM series (pitch: 2.54mm), etc.
- Material Resin part: PPS black (UL94V-0)  
Metal part: Brass
- Finish: Gold plating over nickel base
- Rated voltage: 125V AC,DC
- Rated current: ON-0.5...3A  
ON-0.7...4A  
ON-0.9...6A
- Insulation resistance: 500M Ω or over
- Withstand voltage: 1000V AC, DC per minute
- Operating temperature range: - 40 to + 125℃




■ Example of usage



Combination of ON-0.5 and PM-1



Combination of ON-0.7 and PM-3




Combination of ON-0.9 and PM-7

■ Adaptive socket

Part No.	ON-0.5	ON-0.7	ON-0.9
Adaptive socket	PM-1 PM-10 PM-14 PM-2 PM-5 PM-50 PEM-1 PES-1	PM-3 PM-30 PM-4 PM-40 PM-61 PES-2	PM-7 PM-77

■ Part No.

Part No.	A	B
ON-0.5	0.55	3.7
ON-0.7	0.7	4.0
ON-0.9	0.9	4.0



■ How to order

ON-0.5-10P

↑ Please specify the number of pins. (Maximum number: 20P)  
\*If the number of pins is not specified, we will deliver 20P.